

INDUSTRIAL COMPONENT DATA

SAC-17P-MS/15,0-PVC/FS SCO 1409690 PHOENIX CONTACT

Sensor/actuator cable SAC-17P-MS/15,0-PVC/FS SCO 1409690

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-17P-MS/15,0-PVC/FS SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-17P-MS/15,0-PVC/FS SCO
Catalog number	1409690
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-034A738FC5
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-17P-MS/15,0-PVC/FS SCO - 1409690

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 17-position, PVC, black RAL 9005, Plug straight M12 SPEEDCON, A-coded, on Socket straight M12 SPEEDCON, A-coded, cable length: 15 m

Key Commercial Data

Orderkey 1409690

Packing unit 1

GTIN 4046356873185

Custom tariff number 85444290

Dimensions

Length of cable 15 m

Cable diameter 6.4 mm

Stripping length of the free conductor end 35 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug)

General

Rated current at 40°C 1.5 A

Rated voltage 30 V AC
30 V DC
Number of positions 17
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 HB
Cable
Conductor cross section $17 \times 0.14 \text{ mm}^2$ (Signal line)
AWG signal line 26
Conductor structure signal line $18 \times 0.10 \text{ mm}$
Core diameter including insulation $1 \text{ mm} \pm 0.05 \text{ mm}$ (Signal line)
Wire colors white, brown, green, yellow, gray, pink, blue, red, black, violet, gray-pink, red-blue, white-green, brown-green, white-yellow, yellow-brown, white-gray
Overall twist 17 wires twisted in layers
External sheath, color black RA...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-17P-MS/15,0-PVC/FS SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.