

INDUSTRIAL COMPONENT DATA

SAC-2P- 1,0-547/MINFR 1416455 PHOENIX CONTACT Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P- 1,0-547/MINFR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P- 1,0-547/MINFR
Catalog number	1416455
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-E6FE87153F
Generated	2026-08-04

Product Overview

Power cable

Power Cable, 2-Pole, PVC, Yellow, Free Cable End, to Angled Connection Female 7/8"-16UNF, Cable Length: 1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1416455

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626220130

Weight per Piece (excluding packing) 22.220 g

Custom tariff number 85444290

Country of origin MX (Mexico)

Dimensions

Length of cable 1 m

Ambient conditions

Ambient temperature (operation) -20 °C ... 105 °C (Plug / socket)

Degree of protection IP68

General

Rated current at 40°C 13 A
Rated voltage 300 V AC
300 V DC
Number of positions 2
Color handle area yellow
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display No
Protective circuit/component unwired
Insertion/withdrawal cycles 100
Torque 10 lbf-in.
1.12 Nm
Material
Contact material CuZn
Contact surface material AU
Contact carrier material PVC
Material of grip body PVC
Material, knurls Anodized aluminum
Cable
Cable type ITC/PLTC
Cable abbreviation 547
AWG signal line 18
Conductor cross section signal conductor 2 x AWG 18
Conductor cross section voltage supply 41 x AWG 34
Wire colors Black 1, blue 2, grey 3, brown 4, white 5
External sheath, color yellow
External cable diameter 5.33 mm
Outer sheath, material PVC
Conductor material Bare Cu litz wires
Nominal voltage, cable 300 V
Flame resistance UL 1581, FT4
Other resistance UV resistant (720 h) UL 2556
Ambient temperature (operation) -40 °C ... 105 °C (cable, fixed installation)
-30 °C ... 105 °C (cable, flexible installation)
Standards and Regulations
Flame resistance UL 1581, FT4
Other resistance UV resistant (720 h) UL 2556
Environmental Product Compli...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P- 1,0-547/MINFR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.