

INDUSTRIAL COMPONENT DATA

SAC-2P-500,0-913 1416132 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-500,0-913



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-500,0-913
Catalog number	1416132
Category	Data cable
Minimum order	1 Pcs
Document ID	EO-953DB27DAC
Generated	2026-08-04

Product Overview

Bus system cable

Bus system cable, PROFIBUS PA (31.25 kBit/s), FOUNDATION Fieldbus (31.25 kBit/s), 2-pole, shielded, cable length: 500 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1416132

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626063164

Weight per Piece (excluding packing) 22.220 g

Custom tariff number 85444995

Country of origin NL (Netherlands)

Dimensions

Length of cable 500 m

General

Number of positions 2

Signal type/category PROFIBUS PA, 31.25 kbps

FOUNDATION Fieldbus, 31.25 kbps

Cable

Cable type PROFIBUS PA

Cable type (abbreviation) 913

UL AWM style 2464

Cable structure 2xAWG18/7 + 1xAWG20/7

Conductor cross section 2x 0.75 mm² (Signal line)

1x 0.5 mm² (Drain wire)

AWG signal line 18

Conductor structure signal line 7x 0.40 mm

Core diameter including insulation 2.5 mm ±0.05 mm

Thickness, insulation 0.65 mm

Wire colors Red, green

Twisted pairs 2 cores to the pair

Overall twist One pair with one drain wire and fillers for core

Shielding Aluminum-lined polyester foil and braiding with filler litz wire

Optical shield covering 70 %

External sheath, color black

Outer sheath thickness 1 mm

External cable diameter D 7.8 mm

Tensile strength GRP 80 N

Outer sheath, material PVC

Material conductor insulation Foamed PE

Conductor material Tin-plated Cu litz wires

Conductor resistance 20.5 ?/km (Signal line)

9 ?/km (shield)

Cable capacity 80 nF/km (core-core)

4 nF/km (core-shield)

Signal speed 0.77 c

Cable impedance 100 ? ±20 % (At 31.25 kHz)

Nominal voltage, cable 300 V

Flame resistance according to IEC 60332-1

Resistance to oil According to ICEA S82-552

Other resistance UV resistant According to UL 1581, Secti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-500,0-913 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.