

INDUSTRIAL COMPONENT DATA

SAC-2P- 6,0-PUR/DTFS 1424166 PHOENIX CONTACT

Sensor/actuator cable SAC-2P- 6,0-PUR/DTFS 1424166

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P- 6,0-PUR/DTFS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P- 6,0-PUR/DTFS
Catalog number	1424166
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-7063F25140
Generated	2026-08-04

Product Overview

Sensor/actuator cable - SAC-2P- 6,0-PUR/DTFS - 1424166

Sensor/actuator cable, 2-position, PUR halogen-free, black-gray RAL 7021, cable length: 6 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 2

Material specificationsMaterial of grip body TPU

Electrical propertiesNominal voltage UN 48 V AC

48 V DC

Cable/lineCable length 6 m

PUR halogen-free black [PUR]

Dimensional drawing

Cable weight 33 kg/km

UL AWM Style 20549 / 10493 (80°C/300 V)

Number of positions 2

Shielded no

Cable type PUR halogen-free black [PUR]

Conductor structure signal line 42x 0.15 mm

AWG signal line 18

Conductor cross section 2x 0.75 mm² (Signal line)

Wire diameter incl. insulation 1.69 mm ±0.05 mm (Signal line)

External cable diameter 4.80 mm ±0.15 mm

Outer sheath, material PUR

External sheath, color black-gray RAL 7021

Conductor material Bare Cu litz wires

Material wire insulation PP

Single wire, color brown, blue

Thickness, insulation ≥ 0.21 mm

Thickness, outer sheath ≥ 0.38 mm

Overall twist 2 wires, twisted

Max. conductor resistance ≤ 26 Ω/km (at 20 °C)

Insulation resistance ≥ 1 GΩ*km (at 20 °C)

Nominal voltage, cable ≤ 300 V AC

Test voltage ≥ 3000 V AC (Spark test)

Minimum bending radius, fixed installation 5 x D

Minimum bending radius, flexible installation 10 x D

Smallest bending radius, fixed installation 24 mm

Smallest bending radius, movable installation 48 mm

Dynamic load capacity (bending) Max. bending cycles: 4000000, Bending radius: 48 mm, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s²

Halogen-free in accordance with DIN VDE 0472 part 815

in accordance with DIN EN 50267-2-1

Fla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P- 6,0-PUR/DTFS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.