

INDUSTRIAL COMPONENT DATA

SAC-2P- 7,0-PUR/DTFS 1025856 PHOENIX CONTACT

Sensor/actuator cable SAC-2P- 7,0-PUR/DTFS 1025856

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-7,0-PUR/DTFS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-7,0-PUR/DTFS
Catalog number	1025856
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-59B4AFEF48
Generated	2026-08-04

Product Overview

Sensor/actuator cable - SAC-2P- 7,0-PUR/DTFS - 1025856

Sensor/actuator cable, 2-pole, halogen-free PUR, greyish black RAL 7021, free cable end, to Straight connection female DEUTSCH DT06-2S Clip lock, cable length: 7 m

Sensor/actuator cable, 2-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight DEUTSCH DT06-2S Clip locking, coding: A, cable length: 7 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 2

Material specificationsMaterial of grip body TPU

ConnectorConnection 1

Type free cable end

Connection 2

Type Socket straight DEUTSCH DT06-2S Clip locking

Number of positions 2

Locking type Clip locking

Coding type A

Cable/lineCable length 7 m

PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 33 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 2
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 42x 0.15 mm
AWG signal line 18
Conductor cross section 2x 0.75 mm² (Signal line)
Wire diameter incl. insulation 1.69 mm ±0.05 mm (Signal line)
External cable diameter 4.80 mm ±0.15 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, blue
Thickness, insulation ≥ 0.21 mm
Thickness, outer sheath ≥ 0.38 mm
Overall twist 2 wires, twisted
Max. conductor resistance ≤ 26 Ω/km (at 20 °C)
Insulation resistance ≥ 1 GΩ*km (at 20 °C)
Nominal voltage, cable ≤ 300 V AC
Test voltage ≥ 3000 V AC (Spark test)
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 10 x D
Smallest bending radius, fixed installation 24 mm
Smallest bending radius, movable installation 48 mm
Dynamic load capacity (bending) Max. bending cycles: 4000000, Bending radius: 48 mm, Traversing path: 10 m, Traversing rate: 3 m/s, Acce...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-7,0-PUR/DTFS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.