

INDUSTRIAL COMPONENT DATA

SAC-2P-M 8MR/0,24-PUR/CI-1L-Z 1408500 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-M 8MR/0,24-PUR/CI-1L-Z



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-M 8MR/0,24-PUR/CI-1L-Z
Catalog number	1408500
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-4F92AE3EC8
Generated	2026-08-02

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 2-pole, M8 Elbow Connector, to IC Valve Connectors (9.4mm), with 1 LED, connected with Z-Diode, cable length: 0.24 m

Sensor/actuator cable, 2-position, PUR halogen-free, black-gray RAL 7021, Plug angled M8, on Valve connector CI (9.4 mm), with 1 LED, Wiring: Z diode, cable length: 0.24 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable with valve connector

Number of positions 2

Electrical propertiesNominal voltage UN 24 V AC

24 V DC

Mechanical propertiesMechanical data

Insertion/withdrawal cycles >= 100

ConnectorConnection 1

Type Plug angled M8

Connection 2

Type Valve connector CI (9.4 mm)

Cable/lineCable length 0.24 m

PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 23 kg/km
UL AWM Style 20549
Number of positions 3
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 3x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm ±0.02 mm (Signal line)
External cable diameter 3.85 mm ±0.15 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, blue, black
Thickness, insulation ≥ 0.21 mm (Core insulation)
approx. 0.50 mm (Outer cable sheath)
Overall twist 3 wires, twisted
Max. conductor resistance max. 58 Ω/km (at 20 °C)
Insulation resistance ≥ 100 GΩ*km (at 20 °C)
Nominal voltage, cable ≤ 300 V
Test voltage ≥ 3000 V
Smallest bending radius, fixed installation 19 mm
Smallest bending radius, movable installation 38 mm
Dynamic load capacity (bending) Max. bending cycles: 10000000, Bending radius: 38 mm, Traversing path: 10 m,
Traversing rate: 3 m/s, Acceleration: 10 m/s²
Halogen-free in accordance with DIN VDE 0472 part 815
Flame resista...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-M 8MR/0,24-PUR/CI-1L-Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.