

INDUSTRIAL COMPONENT DATA

SAC-2P-M12MSB/ 0,8-910 1528510 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-M12MSB/ 0,8-910



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-M12MSB/ 0,8-910
Catalog number	1528510
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-1088A8D506
Generated	2026-08-04

Product Overview

Bus system cable

Bus system cable, PROFIBUS, 2-pole halogen-free, shielded, Straight M12 connector, coding: B, to free cable end, cable length: 0.8 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1528510

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918963668

Weight per Piece (excluding packing) 77.400 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 0.8 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 2
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding B - inverse
Signal type/category PROFIBUS
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Material
Flammability rating according to UL 94 V0
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA 6.6
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Cable type PROFIBUS
Cable type (abbreviation) 910
UL AWM style 21198 (80°C/300 V)
Cable structure 1x2xAWG24/19
Conductor cross section $2 \times 0.25 \text{ mm}^2$ (Signal line)
AWG signal line 24
Conductor structure signal line $19 \times 0.13 \text{ mm}$
Core diameter including insulation $2.55 \text{ mm} \pm 0.07 \text{ mm}$
Wire colors Red, green
Overall twist 2 cores with 2 fillers to the core
Shielding Plastic-coated aluminum foil, tinned copper braided shield
Optical shield covering 85 %
External sheath, color violet RAL 4001
External cable diameter $D 7.8 \text{ mm} \pm 0.2 \text{ mm}$
Small...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-M12MSB/ 0,8-910 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.