

INDUSTRIAL COMPONENT DATA

SAC-2P-M12MSB/2-915/M12FSB VA 1402380 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-M12MSB/2-915/M12FSB VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-M12MSB/2-915/M12FSB VA
Catalog number	1402380
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-00C7FFF41B
Generated	2026-08-04

Product Overview

Bus system cable

Bus System Cable, PROFIBUS, 2-Pole, Shielded, Straight Connector M12, Encoding: B, A Straight Female M12, Coding: B, Cable Length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1402380

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356610841

Weight per Piece (excluding packing) 185.900 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 2 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

IP68

IP69K

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 2

Color handle area black

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding B - inverse

Signal type/category PROFIBUS

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 V0

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material PA 6.6

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Stainless steel

Sealing material NBR

Pin assignment

Contact | Color (signal designation) | Contact (optional) 2 (Plug) | GN (A cable) | 2 (Socket)

4 (Plug) | RD (B cable) | 4 (Socket)

Standards and Regulations

Flammability rating according to UL 94 V0

Cable

Cable type PROFIBUS

Cable type (abbreviation) 915

Cable structure 1x2xAWG24/19

Conductor cross section 2x 0.25 mm²

AWG signal line 24

Conductor structure signal line 19x 0.14 mm

Core diameter including insulation 2.56 mm

Wire colors Red, green

Overall twist 2 wires, twisted

Shielding Aluminum-coated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-M12MSB/2-915/M12FSB VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.