

INDUSTRIAL COMPONENT DATA

SAC-2P-M8MS/5,0-PUR/BI-1L-Z180 1237126 PHOENIX CONTACT Sensor/actuator cable, 2-pole, halogen-free PUR, gray..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-M8MS/5,0-PUR/BI-1L-Z180



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-M8MS/5,0-PUR/BI-1L-Z180
Catalog number	1237126
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-34A85A6328
Generated	2026-08-05

Product Overview

Sensor/actuator cable, 2-pole, halogen-free PUR, grayish black RAL 7021, Straight M8 connector, coding: A, to BI valve connector (11 mm), with 1 LED, Circuit: Diode Z, cable length: 5 m, 180° variant

Sensor/actuator cable, 2-pole, halogen-free PUR, grayish black RAL 7021, M8 straight male connector, to BI valve connector (11 mm), with 1 LED, connected with Z diode, cable length: 5 m, 180° variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

ETIM for 1237126 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

2

Type of electrical connection, field-sided (EF005525)

M8

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

M8

Type of plug-in contact, box-sided (EF008386)

Male (plug)

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

5 m

Material of cable sheath (EF004136)

Other

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

Yes

Screened (EF000881)

No

Vulcanize (EF004115)

No

Material contact body (EF008248)

CuSn

Material of contact surface (EF004020)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-25 °C

Rated voltage (EF000228)

24 V

Degree of protection (IP) (EF005474)

IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-M8MS/5,0-PUR/BI-1L-Z180 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.