


INDUSTRIAL COMPONENT DATA

SAC-2P-MICMS/2,0-542 1553917 PHOENIX CONTACT

Sensor/Actuator Cable, 2-Pole, Straight Connector 1/2"-20UNF, t..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-MICMS/2,0-542



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-MICMS/2,0-542
Catalog number	1553917
Category	Sensor-actuator patch cord
Minimum order	250 Pcs
Document ID	EO-6EA6EED94C
Generated	2026-08-01

Product Overview

Sensor/Actuator Cable, 2-Pole, Straight Connector 1/2"-20UNF, to Free Cable End, Cable Length: 2 m
Cable for sensors/actuators
Sensor/actuator cable, 2-position, Plug straight 1/2"-20UNF, on free cable end, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesNumber of positions 2
No. of cable outlets 1
Shielded no
Material specificationsSeal material NBR
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Brass, nickel-plated
ConnectorConnection 1
Type Plug straight 1/2"-20UNF

Number of positions 2
Connection 2
Type free cable end
Cable/lineCable length 2 m
PVC yellow 105 °C [542]
Dimensional drawing
Shielded no
UL AWM Style 2517 (105 °C / 300 V)
Cable weight 32 kg/km
Cable type PVC yellow 105 °C
Short symbol LiYY
Cable type (abbreviation) 542
External cable diameter 4.9 mm ±0.15 mm
Outer sheath, material PVC
External sheath, color yellow
Thickness, outer sheath ≥ 0.76 mm
Conductor material Bare Cu litz wires
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section $2 \times 0.34 \text{ mm}^2$
Material wire insulation PVC
Thickness, insulation ≥ 0.38 mm (Core insulation)
Wire diameter incl. insulation $1.55 \text{ mm} \pm 0.05 \text{ mm}$
Single wire, color brown, blue
Overall twist 2 wires, twisted
Nominal voltage, cable $\leq 300 \text{ V}$
Test voltage, cable $\geq 3000 \text{ V}$
Cable resistance $58 \text{ } \Omega/\text{m}$ (at 20 °C)
Cable insulation resistance $\geq 100 \text{ M}\Omega \cdot \text{km}$ (at 20 °C)
Flame resistance According to DIN EN 60332-1-2
Ambient temperature (operation) -5 °C ... 105 °C (Cable, flexible installation)
-25 °C ... 105 °C (Cable)
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-MICMS/2,0-542 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.