

INDUSTRIAL COMPONENT DATA

SAC-3P- 0,3-PVC/A 1417817 PHOENIX CONTACT

Sensor/actuator cable SAC-3P- 0,3-PVC/A 1417817

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P- 0,3-PVC/A



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P- 0,3-PVC/A
Catalog number	1417817
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-3D6F86A033
Generated	2026-08-04

Product Overview

Sensor/actuator cable - SAC-3P- 0,3-PVC/A - 1417817

Sensor/actuator cable, 3-pole, PVC, black RAL 9005, free cable end, to Valve connector A, cable length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 3-position, PVC, black RAL 9005, free cable end, on Valve connector A, cable length: 0.3 m

Key Commercial Data

Orderkey 1417817

Packing unit 1

GTIN 4055626127101

Custom tariff number 85444290

Dimensions

Length of cable 0.3 m

Ambient conditions

Ambient temperature (operation) -20 °C ... 85 °C (valve plug)

General

Rated current at 40°C 6 A

Rated voltage 230 V

24 V DC

Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Standards/regulations Valve connector EN 175301-803
Status display No
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Material
Flammability rating according to UL 94 V0
Valve plug contact material CuSn
Valve plug contact surface material Sn
Valve plug contact insert material PA 6.6
Material housing valve plug TPU
Sealing material TPU (Seal molded)
Standards and Regulations
Standard designation Valve connector
Standards/regulations EN 175301-803
Flammability rating according to UL 94 V0
Cable
Cable type PVC black
Cable type (abbreviation) PVC
Cable abbreviation LiYY
UL AWM style 2464
Conductor cross section $3 \times 0.5 \text{ mm}^2$
AWG signal line 20
Conductor structure signal line $16 \times 0.20 \text{ mm}$
Core diameter including insulation $1.5 \text{ mm} \pm 0.05 \text{ mm}$
Wire colors black 1, black 2, green/yellow
Overall twist 3 wires, twisted
External sheath, color black RAL 9005
External cable diameter $D 4.8 \text{ mm} \pm 0.2 \text{ mm}$
Minimum bending radius, fixed installation $5 \times D$
Outer sheath, material PVC
Material conductor insulation PVC
Conductor materia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P- 0,3-PVC/A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.