

INDUSTRIAL COMPONENT DATA

SAC-3P-0,5-534/A-1L-Z AE 1423436 PHOENIX CONTACT

Sensor/actuator cable SAC-3P-0,5-534/A-1L-Z AE 1423436

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-0,5-534/A-1L-Z AE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-0,5-534/A-1L-Z AE
Catalog number	1423436
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-9021B3C1CE
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-3P-0,5-534/A-1L-Z AE - 1423436

Sensor/Actuator Cable, 3-Pole, Free Cable End, to Valve Connectors A, with 1 LED, Connected with Z-Diode, Cable Length: 0.5 m, Customer Variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 3-position, PVC, black, free cable end, on Valve connector A, with 1 LED, connected with Z diode, cable length: 0.5 m, Customer version

Key Commercial Data

Orderkey 1423436

Packing unit 1

GTIN 4055626343556

Custom tariff number 85444290

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCI@ss

eCI@ss 6.0 27279200

eCI@ss 7.0 27279218

eCI@ss 9.0 27060311

ETIM

ETIM 5.0 EC001855

ETIM 6.0 EC001855

ETIM 7.0 EC001855

ETIM for 1423436 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

3

Type of electrical connection, field-sided (EF005525)

Other

Positioning cable feed, field-sided (EF005928)

Other

Type of electrical connection, box-sided (EF005524)

Other

Positioning cable feed, box-sided (EF005927)

Other

Cable length (EF000536)

0.5 m

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Black

With LED indication (EF005950)

No

Screened (EF000881)

No

Vulcanize (EF004115)

No

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-5 °C

Rated voltage (EF000228)

24 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-0,5-534/A-1L-Z AE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.