

INDUSTRIAL COMPONENT DATA

SAC-3P-0,5-PUR/M12FS 0,08 1415991 PHOENIX CONTACT

Sensor/actuator cable SAC-3P-0,5-PUR/M12FS 0,15 1415991

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-0,5-PUR/M12FS 0,15



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-0,5-PUR/M12FS 0,15
Catalog number	1415991
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-4FA6E469C0
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-3P-0,5-PUR/M12FS 0,15 - 1415991

Sensor/Actuator Cable, 3-Pole, Halogen-Free PUR, Grey-Black RAL 7021, Free Cable End, to Straight Connecting Female M12, Coding: A, Cable Length: 0.5 m, 150 mm Free End

Sensor/actuator cable, 3-pin, halogen-free, grey-black RAL 7021, free conductor end, on M12 straight socket, coding: A, cable length: 0.5 m, free end 150 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, A-coded, cable length: 0.5 m, 150 mm free end

Key Commercial Data

Orderkey 1415991

Packing unit 1

GTIN 4055626055299

Custom tariff number 85444290

Dimensions

Length of cable 0.5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 250 V AC

250 V DC

Number of positions 3

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y

UL AWM style 20549

Conductor cross section $3 \times 0.34 \text{ mm}^2$ (Signal line)

AWG signal line 22

Conductor structure signal line $42 \times 0.10 \text{ mm}$

Core diameter including insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$ (Signal li...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-0,5-PUR/M12FS 0,15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.