

INDUSTRIAL COMPONENT DATA

SAC-3P- 1,0-PUR/M12FRS PE 1176857 PHOENIX CONTACT

Power cable, 3-pole, halogen-free PUR, black, free cable e..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-1,0-PUR/M12FRS PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-1,0-PUR/M12FRS PE
Catalog number	1176857
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-7C788C0D16
Generated	2026-08-05

Product Overview

Power cable, 3-pole, halogen-free PUR, black, free cable end, to Elbowed Female M12, coding: S, cable length: 1 m, for alternating current up to 16 A/250 V

Power cable, 3-pole, halogen-free PUR, black, free cable end, to Female wired connection M12, encoding: S-encoded, cable length: 1 m, for alternating current up to 16 A/230 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1176857 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

3

Type of electrical connection, field-sided (EF005525)

Other

Positioning cable feed, field-sided (EF005928)

Other

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Female (bus)
Positioning cable feed, box-sided (EF005927)
Angled
Cable length (EF000536)
1 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
Yes
Colour cable sheath (EF008249)
Black
With LED indication (EF005950)
No
Screened (EF000881)
No
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-40 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-25 °C
Rated voltage (EF000228)
690 V
Degree of protection (IP) (EF005474)
IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-1,0-PUR/M12FRS PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.