


INDUSTRIAL COMPONENT DATA

SAC-3P-1,0-PVC/A-1L-Z 1402333 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-1,0-PVC/A-1L-Z



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-1,0-PVC/A-1L-Z
Catalog number	1402333
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-4D89CC94BE
Generated	2026-08-06

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 3-Pole, Free Cable End, to A Valve Connectors, with 1 LED, Connected with Z Diode, Cable Length: 1 m

Sensor/actuator cable, 3-position, PVC, black RAL 9005, free cable end, on Valve connector A, with 1 LED, Wiring: Z diode, cable length: 1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable with valve connector

Number of positions 3

No. of cable outlets 1

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 V0

Seal material TPU

Material housing valve plug TPU

Contact material CuSn

Valve plug contact insert material PA 6.6

Contact surface material Sn
Electrical properties Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 24 V AC
24 V DC
Nominal current IN 4 A
Signaling Status display 1 LED
Status display present Yes
Connector Connection 1
Type free cable end
Connection 2
Type Valve connector A
Number of positions 3
Material CuSn (Contact)
Sn (Contact surface)
PA 6.6 (Contact carriers)
TPU (Housing)
Cable/line Cable length 1 m
PVC black [PVC]
Dimensional drawing
Cable weight 38.6 kg/km
UL AWM Style 2464
Number of positions 3
Shielded no
Cable type PVC black [PVC]
Conductor structure signal line 16x 0.20 mm
AWG signal line 20
Conductor cross section 3x 0.5 mm²
Wire diameter incl. insulation 1.5 mm $\pm 0.05 \text{ mm}$
External cable diameter 4.80 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PVC
External sheath, color black RAL 9005
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color black 1, black 2, green/yellow
Overall twist 3 wires, twisted
Max. conductor resistance 39 Ω/km (at 20 °C)
Insulation resistance $\geq 20 \text{ M}\Omega \cdot \text{km}$
Nominal voltage, cable 300 V
Test voltage 1200 V
Minimum bending radius, fixed installation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-1,0-PVC/A-1L-Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.