

**INDUSTRIAL COMPONENT DATA**

# SAC-3P-10,0-542/M8 FR BK 1406319 PHOENIX CONTACT

## Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-10,0-542/M8 FR BK



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | SAC-3P-10,0-542/M8 FR BK   |
| Catalog number  | 1406319                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 50 Pcs                     |
| Document ID     | EO-B38407E886              |
| Generated       | 2026-08-06                 |

### Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 3-pole, PVC, yellow, free cable end, to Angled Female connection M8, cable length: 10 m

Sensor/actuator cable, 3-position, PVC, yellow, free cable end, on Socket angled M8, coding: A, cable length: 10 m

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                       |
|--------------|-------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial Field Connectivity (IFC) |
|--------------|-------------------------------------------------------|

### Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Application Standard, U.S. cables

Number of positions 3

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au  
Contact carrier material TPU GF  
Material for screw connection Zinc die-cast, nickel-plated  
Outer sheath, material PVC  
Electrical propertiesInsulation resistance  $\geq 100 \text{ M}\Omega$   
Nominal voltage UN 48 V AC  
60 V DC  
Nominal current IN 4 A  
Mechanical propertiesMechanical data  
Insertion/withdrawal cycles  $\geq 100$   
SignalingStatus display no  
Status display present No  
Connection dataConductor connection  
Tightening torque 0.2 Nm (M8 connectors)  
ConnectorConnection 1  
Type free cable end  
Connection 2  
Type Socket angled M8  
Number of positions 3  
Coding type A  
Cable/lineCable length 10 m  
PVC yellow 105 °C [542]  
Dimensional drawing  
Cable weight 21 kg/km  
UL AWM Style 2517 (105 °C / 300 V)  
Number of positions 3  
Shielded no  
Cable type PVC yellow 105 °C [542]  
Conductor structure signal line 32x 1.10 mm  
AWG signal line 24  
Wire diameter incl. insulation 1.12 mm  $\pm 0.03 \text{ mm}$   
External cable diameter 4.10 mm  $\pm 0.2 \text{ mm}$   
Outer sheath, material PVC  
External sheath, color yellow  
Conductor material Tin-plated Cu litz wires  
Material wire insulation PVC  
Single wire, color brown, blue, black...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-10,0-542/M8 FR BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.