

INDUSTRIAL COMPONENT DATA

SAC-3P-10,0-PUR/BI-1L-Z 180 1439670 PHOENIX CONTACT

Cable for sensors/actuators, 3-pole, PUR, black RAL 9005..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-10,0-PUR/BI-1L-Z 180



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-10,0-PUR/BI-1L-Z 180
Catalog number	1439670
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-CB792ABA39
Generated	2026-08-06

Product Overview

Cable for sensors/actuators, 3-pole, PUR, black RAL 9005, end of free cable, to valve Connector BI (11 mm), with 1 LED, connected with Z Diode, cable length: 10 m

Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, free cable end, to BI valve connectors (11mm) / IP65, with 1 LED, connected with Diode Z, cable length: 10 m, Valve connector plug face rotated 180°

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable, sensor-actuator, 3-pin, PUR without halogenated, black-grey RAL 7021, end, handler, free, on plug Connector for valves BI (11 mm), with 1 LED, connected with Z Diode, cable length: 10 m

Commercial data

The code for the order One million four hundred thirty nine thousand six hundred seventy

Pieces/pack. 1 PCS

Sales key BF1DDA -

The amount of minimum order 25 PCS

GTIN Four trillion forty six billion three hundred fifty six million four hundred ninety six thousand nine hundred two

Weight per piece (package included) 301,000 g

Number customs tariff Eighty five million four hundred forty four thousand two hundred ninety

Country of origin PL (Poland)

Size

Length. cable 10 m

General

Rating voltage 24 V AC

24 V DC

N. of poles Three

Cable

Cable type EVEN without halogenated black

Cable type (abbreviation) WHILE

Abbreviation cables Li9Y11Y-HF

UL AWM Style Twenty thousand five hundred forty nine

Conductor cross section 3x 0.5 mm²

Signal line AWG Twenty

Tree conductor signal line 28x 0.15 mm

Wire diameter including insulation 1.5 mm ±0.05 mm (signal Line)

Color wire black 1, black 2, green/yellow

Lay the entire 3 twisted wires longitudinally

External sheath, color grey-black RAL 7021

Cable outer diameter D 4.5 mm ±0.2 mm

Minimum bend radius, fixed 22.5 mm

The number of cycles of bending Fifteen million

Bend radius 50 mm

Positioning movement 0.9 m

Positioning speed 5 m/s

Acceleration 30 m/s²

Outer sheath, material WHILE

Material insulation wire PP

The conductive material Cu wire b...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-10,0-PUR/BI-1L-Z 180 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.