

INDUSTRIAL COMPONENT DATA

SAC-3P- 2,0-500/M 8FS KA 1401044 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-2,0-500/M 8FS KA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-2,0-500/M 8FS KA
Catalog number	1401044
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-B5E538312D
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 3-pole, PVC, grey RAL 7001, free cable end, to straight M8 connection female, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1401044

Packing unit 1

GTIN 4046356519335

Custom tariff number 85444290

Dimensions

Length of cable 2 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 48 V AC
60 V DC
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PVC gray
Cable type (abbreviation) PVC
Cable abbreviation LiYY
Conductor cross section $3 \times 0.25 \text{ mm}^2$ (Signal line)
AWG signal line 24
Conductor structure signal line $14 \times 0.15 \text{ mm}$
Core diameter including insulation $1.17 \text{ mm} \pm 0.05 \text{ mm}$
Thickness, insulation $\geq 0.23 \text{ mm}$ (Core insulation)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
External sheath, color gray
Outer sheath thickness $\geq 0.76 \text{ mm}$
External cable diameter $D 4.2 \text{ mm} \pm 0.15 \text{ mm}$
Cable weight 29 kg/km
Outer sheath, material PVC
Material conductor insulation PVC
Conductor material Bare Cu litz wires
Insulation resistance $\geq 100 \text{ M}\Omega \cdot \text{km}$ (at 20°C)
Conductor resistance max. $79 \text{ }\Omega/\text{km}$ (at 20°C)
Nominal voltage, cable $\geq 300 \text{ V}$
Test voltage, cable $\leq 3 \dots$

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-2,0-500/M 8FS KA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.