

INDUSTRIAL COMPONENT DATA

SAC-3P- 2,0-PVC/M12FS 1413179 PHOENIX CONTACT

Sensor/actuator cable SAC-3P- 2,0-PVC/M12FS 1413179

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P- 2,0-PVC/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P- 2,0-PVC/M12FS
Catalog number	1413179
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-9924997498
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-3P- 2,0-PVC/M12FS - 1413179

Sensor/actuator cable, 3-position, PVC, black RAL 9005, free cable end, on Socket straight M12, coding: A, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 3

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical properties Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Signaling Status display no
Status display present No
Connection data Conductor connection
Tightening torque 0.4 Nm
Connector Connection 1
Type free cable end
Connection 2
Type Socket straight M12
Number of positions 3
Coding type A
Cable/line Cable length 2 m
PVC black [PVC]
Dimensional drawing
Cable weight 40 kg/km
UL AWM Style 2464 / 1729 (80°C/300 V)
Number of positions 3
Shielded no
Cable type PVC black [PVC]
Conductor structure signal line 19x 0.15 mm
AWG signal line 22
Conductor cross section $3 \times 0.34 \text{ mm}^2$ (Signal line)
Wire diameter incl. insulation $1.26 \text{ mm} \pm 0.05 \text{ mm}$
External cable diameter $4.30 \text{ mm} \pm 0.2 \text{ mm}$
Outer sheath, material PVC
External sheath, color black RAL 9005
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color brown, blue, black
Thickness, insulation $\geq 0.23 \text{ mm}$ (Core insulation)
Thickness, outer sheath $\geq 0.76 \text{ mm}$
Overall twist 3 wir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P- 2,0-PVC/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.