

INDUSTRIAL COMPONENT DATA

SAC-3P-3,0-PUR/A-1L-R VA 1417259 PHOENIX CONTACT

Sensor/actuator cable SAC-3P-3,0-PUR/A-1L-R VA 1417259

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-3,0-PUR/A-1L-R VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-3,0-PUR/A-1L-R VA
Catalog number	1417259
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-2A7F66D9F8
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-3P-3,0-PUR/A-1L-R VA - 1417259

Sensor/actuator cable, 3-pole halogen-free, free cable end, to Valve connectors A, with 1 LED, connected to free-flowing diode, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Valve connector A, with 1 LED, connected with Damping diode, cable length: 3 m

Key Commercial Data

Orderkey 1417259

Packing unit 1

GTIN 4055626077390

Custom tariff number 85444290

Dimensions

Length of cable 3 m

Ambient conditions

Ambient temperature (operation) -20 °C ... 85 °C (valve plug)

General

Rated current at 40°C 2 A

Rated voltage 24 V DC
24 V DC
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Standards/regulations Valve connector EN 175301-803
Status display 1 LED
Protective circuit/component Damping diode
Overvoltage category III
Degree of pollution 3
Material
Flammability rating according to UL 94 V0
Valve plug contact material CuSn
Valve plug contact surface material Sn
Valve plug contact insert material PA 6.6
Material housing valve plug TPU
Material, knurls Stainless steel
Sealing material TPU (Seal molded)
Standards and Regulations
Standard designation Valve connector
Standards/regulations EN 175301-803
Flammability rating according to UL 94 V0
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section $3 \times 0.5 \text{ mm}^2$
AWG signal line 20
Conductor structure signal line $28 \times 0.15 \text{ mm}$
Core diameter including insulation $1.5 \text{ mm} \pm 0.05 \text{ mm}$ (Signal line)
Wire colors black 1, black 2, green/yellow
Overall twist 3 wires, twisted
External sheath, color black-gray RAL 7021
External cable diameter D 4.5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-3,0-PUR/A-1L-R VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.