

INDUSTRIAL COMPONENT DATA

SAC-3P- 5,0-100/M 8FS 1505038 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P- 5,0-100/M 8FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P- 5,0-100/M 8FS
Catalog number	1505038
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-4D200F9873
Generated	2026-08-06

Product Overview

Sensor/actuator cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1505038

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4017918848446

Weight per Piece (excluding packing) 134.100 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 3

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR/PVC gray

Cable type (abbreviation) 100

Cable abbreviation LiYY-11Y

Conductor cross section 0.25 mm^2

AWG signal line 24

Conductor structure signal line $32 \times 0.10 \text{ mm}$ Core diameter including insulation $1.32 \text{ mm} \pm 0.02 \text{ mm}$ Thickness, insulation $\geq 0.23 \text{ mm}$ (Core insulation) $\geq 0.38 \text{ mm}$ (Outer cable sheath)approx. $3.5 \text{ mm} \pm 0.1 \text{ mm}$ (Inner sheath)

Wire colors brown, blue, black

Overall twist 3 wires, twisted

External sheath, color gray RAL 7001

External cable diameter $D 4.4 \text{ mm} \pm 0.2 \text{ mm}$

Smallest bending radius, fixed installation 22 mm

Smallest bending radius, movable installation 44 mm

Number of b...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P- 5,0-100/M 8FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.