

INDUSTRIAL COMPONENT DATA

SAC-3P-M 8MS/ 2,0-PUR/M 8FR 1501317 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M 8MS/ 2,0-PUR/M 8FR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M 8MS/ 2,0-PUR/M 8FR
Catalog number	1501317
Category	Sensor-actuator patch cord
Minimum order	5 Pcs
Document ID	EO-816ACB1139
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, Straight M8 connector, coding: A, to Elbowed female M8, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1501317

Packing unit 5 pc

Minimum order quantity 25 pc

Note Made to Order (non-returnable)

GTIN 4017918613549

Weight per Piece (excluding packing) 44.560 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 2 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Torque 0.2 Nm (M8 connectors)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section $3 \times 0.25 \text{ mm}^2$
AWG signal line 24
Conductor structure signal line $32 \times 0.10 \text{ mm}$
Core diameter including insulation $1.17 \text{ mm} \pm 0.02 \text{ mm}$
Thickness, insulation $\geq 0.21 \text{ mm}$ (Core insulation)
Wire colors brown, b...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M 8MS/ 2,0-PUR/M 8FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.