

INDUSTRIAL COMPONENT DATA

SAC-3P-M 8MS/ 5,5-PUR/M 8FR 1501320 PHOENIX CONTACT

Cable for sensors/actuators, 3-pole, PUR halogen-free, b..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M 8MS/ 5,5-PUR/M 8FR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M 8MS/ 5,5-PUR/M 8FR
Catalog number	1501320
Category	Sensor-actuator patch cord
Minimum order	5 Pcs
Document ID	EO-10B79C8EB4
Generated	2026-08-05

Product Overview

Cable for sensors/actuators, 3-pole, PUR halogen-free, black-gray RAL 7021, male Connector straight M8, to Female connection angled M8, cable length: 5,5 m

Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, Straight male connector M8, to Angled connection female M8, cable length: 5.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Cable, sensor-actuator, 3-pin, PUR without halogenated, black-grey RAL 7021, Male straight M8, on Female angled M8, cable length: 5,5 m

Commercial data

The code for the order One million five hundred one thousand three hundred twenty

Pieces/pack. 5 PCS

Sales key BF1BBA -

The amount of minimum order 25 PCS

GTIN Four trillion seventeen billion nine hundred eighteen million six hundred thirteen thousand five hundred thirty two

Weight per piece (package included) 115,380 g

Number customs tariff Eighty five million four hundred forty four thousand two hundred ninety

Country of origin DE (Germany)

Size

Length. cable 5.5 m
Environmental conditions
Degree of protection IP65
IP67
IP68
General
Rated current at 40 °C 4 To
Rating voltage 48 V AC
60 V DC
N. of poles Three
Insulation resistance $\geq 100 \text{ M}\Omega$
Encoding A - standard
Signalling status of No
Overvoltage category II
Pollution degree Three
Material
Class behaviour according to UL 94 HB
Contact material CuSn
Material surface contacts Ni/Au
Insert material latch TPU GF
Material handles TPU, hardly inflammable, self-extinguishing
Nut material Zinc die-cast, nickel-plated
Material gasket NBR
Regulations and requirements
Class behaviour according to UL 94 HB
Cable
Cable type EVEN without halogenated black
Cable type (abbreviation) WHILE
Abbreviation cables Li9Y11Y-HF
UL AWM Style Twenty thousand five hundred forty nine
Conductor cross section $3 \times 0.25 \text{ mm}^2$
Signal line AWG Twenty four
Tree conductor signal line $32 \times 0.10 \text{ mm}$
Wire diameter inclu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M 8MS/ 5,5-PUR/M 8FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.