


INDUSTRIAL COMPONENT DATA

SAC-3P-M 8MS/ 6,0-PUR 1501508 PHOENIX CONTACT

Sensor/actuator cable SAC-3P-M 8MS/ 6,0-PUR 1501508

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M 8MS/ 6,0-PUR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M 8MS/ 6,0-PUR
Catalog number	1501508
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-45A3196229
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-3P-M 8MS/ 6,0-PUR - 1501508

Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, M8 straight male connector, to free cable end, cable length: 6 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M8, on free cable end, cable length: 6 m

Key Commercial Data

Orderkey 1501508

Packing unit 1

GTIN 4017918613495

Custom tariff number 85444290

Dimensions

Length of cable 6 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 3

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Status display No

Material

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF

UL AWM style 20549

Conductor cross section $3 \times 0.25 \text{ mm}^2$

AWG signal line 24

Conductor structure signal line $32 \times 0.10 \text{ mm}$

Core diameter including insulation $1.17 \text{ mm} \pm 0.02 \text{ mm}$

Thickness, insulation $\geq 0.21 \text{ mm}$ (Core insulation)

Wire colors brown, blue, black

Overall twist 3 wires, twisted

Length of twist, overall twist 40 mm

External sheath, color black-gray RAL 7021

Outer sheath thickness approx. 0.5 mm

External cable diameter $D 3.6 \text{ mm} \pm 0.15 \text{ mm}$

Smallest bending radius, fixed installation 18 mm

Smallest bending radius, movable installation 36 mm

Number of bending cycles 10000000

Bending radius 44 mm

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 10 m/s^2

Cable weight...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M 8MS/ 6,0-PUR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.