

## INDUSTRIAL COMPONENT DATA

# SAC-3P-M 8Y/2XM 8FS HEK 1415096 PHOENIX CONTACT Y distributor SAC-3P-M 8Y/2XM 8FS HEK 1415096

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M 8Y/2XM 8FS HEK



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | PHOENIX CONTACT         |
| MPN / Reference | SAC-3P-M 8Y/2XM 8FS HEK |
| Catalog number  | 1415096                 |
| Category        | Sensor actuator adapter |
| Minimum order   | 100 Pcs                 |
| Document ID     | EO-65B3D89BC6           |
| Generated       | 2026-08-06              |

## Product Overview

Y distributor - SAC-3P-M 8Y/2XM 8FS HEK - 1415096

Y-splitter, 3-pole, M8 straight connector, coding: A, a M8 straight female and M8 straight female, Customer variant

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Industrial Field Connectivity (IFC)

## Additional Product Information

Y distributor, 3-position, Plug straight M8, on Socket straight M8 and Socket straight M8, Customer version

Key Commercial Data

Orderkey 1415096

Packing unit 1

GTIN 4055626039107

Custom tariff number 85366990

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

General

Rated current at 40°C 4 A

Rated voltage 60 V

Number of positions 3

Insulation resistance &gt;= 10 G?

Coding A - standard

Standards/regulations M8 connector IEC 61076-2-104

M8 connector IEC 61076-2-104

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles  $\geq 100$

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M8 connector

Standards/regulations IEC 61076-2-104

Standard designation M8 connector

Standards/regulations IEC 61076-2-104

Flammability rating according to UL 94 HB

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 5.1 27061800

eCl@ss 6.0 27279200

eCl@ss 7.0 27440104

eCl@ss 8.0 27440104

eCl@ss 9.0 27440106

ETIM

ETIM 5.0 EC002062

ETIM 6.0 EC002925

ETIM 7.0 EC002925

UNSPSC

UNSPSC 13.2 31251501

ETIM for 1415096 Sensors (E...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M 8Y/2XM 8FS HEK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.