

INDUSTRIAL COMPONENT DATA

SAC-3P-M12MR/ 5,0-280 VC 1080932 PHOENIX CONTACT

Sensor/actuator cable SAC-3P-M12MR/ 5,0-280 VC 1080932

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MR/ 5,0-280 VC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MR/ 5,0-280 VC
Catalog number	1080932
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-75A424A800
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-3P-M12MR/ 5,0-280 VC - 1080932

Sensor/actuator cable, 3-pole, halogen-free PUR, grey RAL 7001, Angled male connector M12, coding: A, to free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, gray RAL 7001, Plug angled M12, A-coded, on free cable end, cable length: 5 m

Key Commercial Data

Orderkey 1080932

Packing unit 1

GTIN 4055626806938

Custom tariff number 85444290

Dimensions

Length of cable 5 m

Ambient conditions

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Overvoltage category II
Degree of pollution 3
Torque 0.4 Nm
Standards and Regulations
Flame resistance according to DIN VDE 0482
According to DIN EN 50265-2-1
Resistance to oil largely oil-resistant
Cable
Cable type PUR halogen-free gray
Cable type (abbreviation) 280
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section $3 \times 0.5 \text{ mm}^2$ (Signal line)
AWG signal line 20
Conductor structure signal line $28 \times 0.15 \text{ mm}$
Core diameter including insulation $1.5 \text{ mm} \pm 0.05 \text{ mm}$ (Signal line)
Wire colors black 1, black 2, green/yellow
Overall twist Wires twisted in layers
External sheath, color gray RAL 7001
External cable diameter $D 4.5 \text{ mm} \pm 0.2 \text{ mm}$
Smallest bending radius, fixed installation 22.5 mm
Number of bending cycles 15000000
Bending radius 50 mm
Traversing path 0.9 m
Traversing rate 5 m/s
Acceleration 30 m/s^2
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance $\geq 20 \text{ M}\Omega \cdot \text{km}$
Conductor resistance $39 \text{ m}\Omega/\text{km}$ (at 20 °C)
Nominal voltage, cable 300 V
Test voltage, cable 12...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MR/ 5,0-280 VC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.