

INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS/0,6-PUR/A-1L-Z110 1400738 PHOENIX

CONTACT Sensor/actuator cable

SAC-3P-M12MS/0,6-PUR/A-1L-Z110 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS/0,6-PUR/A-1L-Z110



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS/0,6-PUR/A-1L-Z110
Catalog number	1400738
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-55E4BF8DB8
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-3P-M12MS/0,6-PUR/A-1L-Z110 - 1400738

Sensor/actuator cable, 3-pole, halogen-free PUR, grayish black RAL 7021, Straight male connector M12, coding: A, to Valve connector A, with 1 LED, connected with Diode Z, cable length: 0.6 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, on Valve connector A, with 1 LED, connected with Z diode, cable length: 0.6 m

Key Commercial Data

Orderkey 1400738

Packing unit 1

GTIN 4046356510264

Custom tariff number 85444290

Dimensions

Length of cable 0.6 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

-20 °C ... 85 °C (valve plug)
Degree of protection IP65
IP67
General
Rated current at 40°C 4 A
Rated voltage 110 V AC
110 V DC
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Valve connector EN 175301-803
Status display 1 LED
Protective circuit/component Z diode
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100 (M12 connector)
Torque 0.4 Nm (M12 connector)
0.6 Nm (Valve connector)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU
Valve plug contact material CuSn
Valve plug contact surface material Sn
Valve plug contact insert material PA 6.6
Material housing valve plug TPU
Material, knurls Zinc die-cast, nickel-plated
Sealing material TPU (Seal molded)
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Standard designation Valve connector
Standards/regulations EN 175301-803
Flammability rating according to UL 94 HB
Cable....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS/0,6-PUR/A-1L-Z110 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.