

INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS/0,9-PUR/A-1L-Z 1439557 PHOENIX CONTACT

Cable for sensors/actuators, PUR halogen-free, black-gra..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS/0,9-PUR/A-1L-Z



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS/0,9-PUR/A-1L-Z
Catalog number	1439557
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-08EA791582
Generated	2026-08-05

Product Overview

Cable for sensors/actuators, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coded, to valve Connector A, with 1 LED, connected with Z Diode, cable length: 0.9 m

Sensor/actuator cable, halogen-free PUR, grayish black RAL 7021, Straight male connector M12, coding: A, a Valve connector A, with 1 LED, connected with Diode Z, cable length: 0.9 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Cable for sensors/actuators, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coded, to valve Connector A, with 1 LED, connected with Z Diode, cable length: 0.9 m

Data commercial

Key order One million four hundred thirty nine thousand five hundred fifty seven

Packing unit 1 pcs

Key selling BF1DJA -

EAN Four trillion forty six billion three hundred fifty six million four hundred eighty nine thousand four hundred nine

Unit weight (excluding packaging) 60,000 g

Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety

Country of origin PL (Poland)

Measures

Cable length 0.9 m

Environmental conditions

Room temperature (service)

Index of protection IP65

IP67

Overview

Current sizing at 40 °C 4 To

Tension sizing 24 V AC

24 V DC

Status indication 1 LED

Protective circuit/component protection Diode Z

Category surge III

Pollution degree Three

Cycles of plug ≥ 100

Material

Class of flammability according to UL 94 HB

Standards and specifications

Class of flammability according to UL 94 HB

Cable

Type of cable PUR halogen-free black

Cable type (abbreviation) PUR

Abbreviation of cable Li9Y11Y-HF

UL AWM Style Twenty thousand five hundred forty nine

Section of driver 3x 0.5 mm²

Signal cable AWG Twenty

Construction of the driver signal cable 28x 0.15 mm

Diameter of the conductors, insulation included 1.5 mm ± 0.05 mm (conductor signals)

Colors driver black 1, black 2, green/yellow

Cabling total 3-conductor longitudinally twisted

Outer wrap, color black...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS/0,9-PUR/A-1L-Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.