

INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS/ 1,0-170/M12FS 1538490 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS/ 1,0-170/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS/ 1,0-170/M12FS
Catalog number	1538490
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-03753F83CE
Generated	2026-08-05

Product Overview

Sensor/actuator cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1538490

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356075435

Weight per Piece (excluding packing) 42.400 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 1 m

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Torque 0.4 Nm
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y
UL AWM style 20549
Conductor cross section $3 \times 0.34 \text{ mm}^2$ (Signal line)
AWG signal line 22
Conductor structure signal line $42 \times 0.10 \text{ mm}$
Core diameter including insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$ (Signal line)
Thickness, insulation $\geq 0.21 \text{ mm}$ (Core insulation)
approx. 0.5 mm (Outer cable sheath)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
External sheath, color black-gray RAL 7021
External cable diameter $D 3.85 \text{ mm} \pm 0.15 \text{ mm}$
Smallest bending radius, fixed installation 19 mm
Smallest bending radius, movab...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS/ 1,0-170/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.