

INDUSTRIAL COMPONENT DATA

**SAC-3P-M12MS/10,0-500/A-1L-Z 1438943 PHOENIX CONTACT
Sensor/actuator cable SAC-3P-M12MS/10,0-500/A-1L-Z 1438..**

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS/10,0-500/A-1L-Z



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS/10,0-500/A-1L-Z
Catalog number	1438943
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-CDA7BEEAE6
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-3P-M12MS/10,0-500/A-1L-Z - 1438943

Sensor/Actuator Cable, 3-Pole, M12 Straight Connector, Coding: A, with 1 LED, Connected with Diode Z, to Valve Connectors A, with 1 LED, Connected with Diode Z, Cable Length: 10 m

Sensor/actuator cable, 3-position, PVC, gray RAL 7001, Plug straight M12, coding: A, with 1 LED, on Valve connector A, with 1 LED, Wiring: Z diode, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable with valve connector

Number of positions 3

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material TPU

Material housing valve plug TPU

Material of grip body TPU
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Contact material CuSn
Valve plug contact insert material PA 6.6
Contact surface material Sn
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 24 V AC
24 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100 (M12 connector)
SignalingStatus display 1 LED
Status display present Yes
ConnectorConnection 1
Type Plug straight M12
Number of positions 3
Coding type A
Connection 2
Type Valve connector A
Number of positions 3
Material CuSn (Contact)
Sn (Contact surface)
PA 6.6 (Contact carriers)
TPU (Housing)
Cable/lineCable length 10 m
PVC gray [500]
Dimensional drawing
Cable weight 39.2 kg/km
Number of positions 3
Shielded no
Cable type PVC gray [500]
Conductor type Round cable
Conductor structure signal line 16x 0.20 mm
AWG signal line 20
Conductor cross section 3x 0.5 mm² (Signal line)
Wire diameter incl. insulation 1.5 mm ± 0.05 mm (Signal line)
External cable diameter 4.80 mm ± 0.2 mm
Outer sheath, material PVC
Ex...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS/10,0-500/A-1L-Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.