

INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS/1,5-PUR/M 8FS 1X4 1105823 PHOENIX CONTACT Sensor/actuator cable, 3-position, PUR halogen-free, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS/1,5-PUR/M 8FS 1X4



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS/1,5-PUR/M 8FS 1X4
Catalog number	1105823
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-2601DABA0B
Generated	2026-08-05

Product Overview

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, on Socket straight M8, cable length: 0.3 m, Customer version

Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, M12 straight male connector, coding: A, to M8 straight connection female, cable length: 0.3 m, Customer variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1105823

Packing unit 1

GTIN 4055626990361

Custom tariff number 85444290

Drawings

Ambient conditions

Cable

Classifications

Dimensions

General

[Environmental Product Compliance](#)

[Drawings](#)

[Cable cross section](#)

[PUR halogen-free black \[PUR\]](#)

[Back to top](#)[Dimensions](#)

[Length of cable 0.3 m](#)

[Back to top](#)[Ambient conditions](#)

[Degree of protection IP65](#)

[IP67](#)

[IP68](#)

[Back to top](#)[General](#)

[Rated current at 40°C 4 A](#)

[Rated voltage 48 V AC](#)

[60 V DC](#)

[Number of positions 3](#)

[Overvoltage category II](#)

[Degree of pollution 3](#)

[Torque 0.4 Nm](#)

[0.2 Nm](#)

[Back to top](#)[Cable](#)

[Cable type PUR halogen-free black](#)

[Cable type \(abbreviation\) PUR](#)

[Cable abbreviation Li9Y11Y-HF](#)

[UL AWM style 20549 / 10493 \(80°C/300 V\)](#)

[Conductor cross section 3x 0.25 mm²](#)

[AWG signal line 24](#)

[Conductor structure signal line 32x 0.10 mm](#)

[Core diameter including insulation 1.17 mm ±0.02 mm](#)

[Thickness, insulation ≥ 0.21 mm \(Core insulation\)](#)

[Wire colors brown, blue, black](#)

[Overall twist 3 wires, twisted](#)

[Length of twist, overall twist 40 mm](#)

[External sheath, color black-gray RAL 7021](#)

[Outer sheath thickness approx. 0.5 mm](#)

[External cable diameter D 3.6 mm ±0.15 mm](#)

[Smallest bending radius, fixed installation 18 mm](#)

[Smallest bending radius, movable installation 36 mm](#)

[Number of bending cycles 10000000](#)

[Bending radius 44 mm](#)

[Traversing path 10 m](#)

[Traversing rate 3 m/s](#)

[Acceleration 10 m/s²](#)

[Cable weight 18 kg/km](#)

[Outer sheath, material PUR](#)

[Material conductor insulation PP](#)

[Conductor material Bare Cu litz wires](#)

Insulation resistance $\geq 100 \text{ G}\cdot\text{km}$ (at 20 °C)

Cond...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS/1,5-PUR/M 8FS 1X4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.