

INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS/2,4-PUR/M12FS 1X3 1630795 PHOENIX CONTACT Sensor/actuator cable, 3-pole, halogen-free PUR, grey..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS/2,4-PUR/M12FS 1X3



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS/2,4-PUR/M12FS 1X3
Catalog number	1630795
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-0D7FA5F0A2
Generated	2026-08-05

Product Overview

Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, Straight connector M12, coding: A, to Straight female M12, coding: A, cable length: 2.4 m

Cable for sensors/actuators

Sensor/actuator cable, 3-position, Plug straight M12, coding: A, on Socket straight M12, coding: A, cable length: 2.4 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 3

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display No
Status display present No
Connection dataPin assignment
Contact | Color (signal designation) | Contact (optional) 3 (Plug) | BU | 1 (Socket)
1 (Plug) | BN | 3 (Socket)
4 (Plug) | BK | 4 (Socket)
ConnectorConnection 1
Type Plug straight M12
Number of positions 3
Coding type A
Connection 2
Type Socket straight M12
Number of positions 3
Coding type A
Cable/lineCable length 2.4 m
PUR halogen-free black [PUR]
Dimensional drawing
Shielded no
UL AWM Style 20549
Cable weight 23 kg/km
Cable type PUR halogen-free black
Short symbol Li9Y11Y
Cable type (abbreviation) PUR
External cable diameter 3.85 mm $\pm 0.15 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Conductor structure signal line 42x 0.10 mm
AWG s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS/2,4-PUR/M12FS 1X3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.