

INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS4P/1,5-PUR SH2 1426484 PHOENIX CONTACT

Sensor/actuator cable SAC-3P-M12MS4P/1,5-PUR SH2 1426484

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS4P/1,5-PUR SH2



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS4P/1,5-PUR SH2
Catalog number	1426484
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-E6D86BD401
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-3P-M12MS4P/1,5-PUR SH2 - 1426484

Sensor/actuator cable, 4-position halogen-free, shielded, Plug straight M12, coding: A, on free cable end, cable length: 1.5 m, Customer version

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 4

Electrical propertiesNominal voltage UN 48 V AC

60 V DC

ConnectorConnection 1

Type Plug straight M12

Number of positions 4

Coding type A

Number of positions 4

Connection 2

Type free cable end

Cable/line Cable length 1.5 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 26 kg/km
UL AWM Style 20549
Number of positions 3
Shielded yes
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 32x 0.10 mm
AWG signal line 24
Conductor cross section 3x 0.25 mm² (Signal line)
Wire diameter incl. insulation 1.17 mm ±0.02 mm (Signal line)
External cable diameter 4.35 mm ±0.2 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, blue, black
Thickness, insulation ≥ 0.21 mm (Core insulation)
≥ 0.5 mm (Outer cable sheath)
Overall twist 3 wires, twisted
Optical shield covering 80 %
Max. conductor resistance max. 79 ?/km
Insulation resistance ≥ 100 G?·km
Nominal voltage, cable 300 V
Test voltage 3000 V
Smallest bending radius, fixed installation 22 mm
Smallest bending radius, movable installation 44 mm
Max. bending cycles 10000000
Halogen-free in accordance with DIN VDE 0472 part 815
Flame resistance in accordance with UL 758/1581 FT2
DIN EN 60332-2-2 (20 s)
Resistance to oil in accordance with DIN EN 60811-2-1
Other resistance Highly resistant to acids, alkaline solut...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS4P/1,5-PUR SH2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.