

INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS4P/3,5PUR/M8FS 2-4 1076611 PHOENIX CONTACT Sensor/actuator cable

SAC-3P-M12MS4P/3,5PUR/M8FS 2-4 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS4P/3,5PUR/M8FS 2-4



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS4P/3,5PUR/M8FS 2-4
Catalog number	1076611
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-CC137BA718
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-3P-M12MS4P/3,5PUR/M8FS 2-4 - 1076611

Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, M12 straight male connector, encoding: A, to M8 straight connection female, coding: A, cable length: 3.5 m, Special connection: 1-1; 2-4; 3-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, on Socket straight M8, A-coded, cable length: 3.5 m, Special wiring: 1-1; 2-4; 3-3

Key Commercial Data

Orderkey 1076611

Packing unit 1

GTIN 4055626784069

Custom tariff number 85444290

Dimensions

Length of cable 3.5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 3

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

M8 connector IEC 61076-2-104

Status display No

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Standard designation M8 connector

Standards/regulations IEC 61076-2-104

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF

UL AWM style 20549

Conductor cross section $3 \times 0.25 \text{ mm}^2$

AWG signal line 24

Conductor structure signal line $32 \times 0.10 \text{ mm}$

Core diameter including insu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS4P/3,5PUR/M8FS 2-4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.