

INDUSTRIAL COMPONENT DATA

SAC-3P-M12MSS/ 2,5-PVC PE 1425622 PHOENIX CONTACT

Power Cable, 3-pin, PVC, black, Connector, male straight M..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MSS/ 2,5-PVC PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MSS/ 2,5-PVC PE
Catalog number	1425622
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-575FFEFFAE
Generated	2026-08-06

Product Overview

Power Cable, 3-pin, PVC, black, Connector, male straight M12 SPEEDCON, Encoded S, end of free cable, cable length: 2.5 m, for ac current up to 16 A/230 V

Power cable, 3-pole, Straight M12 connector, coding: S, to free cable end, cable length: 2.5 m, for alternating current up to 16 A/230 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1425622 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

3

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

Other

Positioning cable feed, box-sided (EF005927)

Other

Cable length (EF000536)

2.5 m

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Black

With LED indication (EF005950)

No

Screened (EF000881)

No

Vulcanize (EF004115)

No

Material contact body (EF008248)

Other

Material of contact surface (EF004020)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-5 °C

Rated voltage (EF000228)

690 V

Degree of protection (IP) (EF005474)

IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MSS/ 2,5-PVC PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.