

INDUSTRIAL COMPONENT DATA

SAC-3P-M12Y/2X0,3-PUR/M12FS 1077271 PHOENIX CONTACT

Sensor/actuator cable SAC-3P-M12Y/2X0,3-PUR/M12FS 1077271

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12Y/2X0,3-PUR/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12Y/2X0,3-PUR/M12FS
Catalog number	1077271
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-6EF123541D
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-3P-M12Y/2X0,3-PUR/M12FS - 1077271

Sensor/Actuator Cable, 3-Pole, M12 Straight Connector, A, A, to M12 Straight Female, A12 Encoding, M12 Straight Female, A-Encoding, Cable Length: 0.3 m

Sensor/actuator cable, 3-pin, halogen-free, grey-black RAL 7021, straight male M12, coding: A, on straight socket M12, coding: A and straight socket M12, coding: A, cable length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, on Socket straight M12, A-coded and Socket straight M12, A-coded, cable length: 0.3 m

Key Commercial Data

Orderkey 1077271

Packing unit 1

GTIN 4055626789897

Custom tariff number 85444290

Dimensions

Length of cable 0.3 m

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 3

Insulation resistance $\geq 10\text{ G}\Omega$

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y

UL AWM style 20549

Conductor cross section $3 \times 0.34\text{ mm}^2$ (Signal line)

AWG signal line 22

Conductor structure signal line $42 \times 0.10\text{ mm}$

Core diameter including insulation $1.27\text{ mm} \pm 0.02\text{ mm}$ (Signal line)

Thickness, insulation $\geq 0.21\text{ mm}$ (Core insulation)

approx. 0.5 mm (Outer cable sheath)

Wire colors brown, blue, black

Overall twist 3 wires, twisted

External sheath, color black-gray RAL 7021

External cable diameter $D\ 3.85\text{ mm} \pm 0.15\text{ mm}$

Smallest bending radius, fixed installation 19 mm

Smallest bending radius, mo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12Y/2X0,3-PUR/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.