

INDUSTRIAL COMPONENT DATA

SAC-3P-M12Y/2X0,4PUR/M12FS KAS 1401357 PHOENIX CONTACT Sensor/actuator cable, PUR halogen-free, black-gray R..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12Y/2X0,4PUR/M12FS KAS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12Y/2X0,4PUR/M12FS KAS
Catalog number	1401357
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-D1098BC4DE
Generated	2026-08-03

Product Overview

Sensor/actuator cable, PUR halogen-free, black-gray RAL 7021
Cable for sensors/actuators

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Distributor with cable
Electrical propertiesNominal voltage UN 48 V AC
60 V DC
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 100
Cable/linePUR halogen-free black [PUR]
Dimensional drawing
Cable weight 23 kg/km
UL AWM Style 20549
Number of positions 3
Shielded no
Cable type PUR halogen-free black [PUR]

Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 3x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm ±0.02 mm (Signal line)
External cable diameter 3.85 mm ±0.15 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, blue, black
Thickness, insulation ≥ 0.21 mm (Core insulation)
approx. 0.50 mm (Outer cable sheath)
Overall twist 3 wires, twisted
Max. conductor resistance max. 58 Ω/km (at 20 °C)
Insulation resistance ≥ 100 GΩ*km (at 20 °C)
Nominal voltage, cable ≤ 300 V
Test voltage ≥ 3000 V
Smallest bending radius, fixed installation 19 mm
Smallest bending radius, movable installation 38 mm
Dynamic load capacity (bending) Max. bending cycles: 10000000, Bending radius: 38 mm, Traversing path: 10 m,
Traversing rate: 3 m/s, Acceleration: 10 m/s²
Halogen-free in accordance with DIN VDE 0472 part 815
Flame resistance in accordance with UL 758/1581 FT2
DIN EN 60332-2-2 (20 s)
Resistance to oil in accordance with DIN EN 60811-2-1
Other resistance Highly resistant...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12Y/2X0,4PUR/M12FS KAS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.