

INDUSTRIAL COMPONENT DATA

SAC-3P-M12Y/2X4,0-140 1502484 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12Y/2X4,0-140



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12Y/2X4,0-140
Catalog number	1502484
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-1658A36F5E
Generated	2026-08-06

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 3-Pole, PUR/PVC, Yellow, M12 Straight Male Connector, Coding: A, To Free Cable End, Cable Length: 4 m

Sensor/actuator cable, 3-position, PUR/PVC, yellow, Plug straight M12, coding: A, on free cable end, cable length: 4 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Distributor with cable

Number of positions 3

No. of cable outlets 2

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance $\geq 10\text{ G}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
ConnectorConnection 1
Type Plug straight M12
Coding type A
Connection 2
Type free cable end
Cable/lineCable length 4 m
PUR/PVC yellow [140]
Dimensional drawing
Cable weight 37 kg/km
Number of positions 3
Shielded no
Cable type PUR/PVC yellow [140]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 0.34 mm²
Wire diameter incl. insulation 1.52 mm $\pm 0.02\text{ mm}$
External cable diameter 5.20 mm $\pm 0.2\text{ mm}$
Outer sheath, material PUR
External sheath, color yellow
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color brown, blue, black
Thickness, insulation $\geq 0.23\text{ mm}$ (Core insulation)
 $\geq 0.38\text{ mm}$ (Outer cable sheath)
approx. 0.45 mm (Inner sheath)
Overall twist 3 wires, twisted
Max. conductor resistance max. 57.3 Ω/km (at 20...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12Y/2X4,0-140 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.