

INDUSTRIAL COMPONENT DATA

SAC-3P-M8FY/2X0,3-PUR/M 8MS 1057311 PHOENIX CONTACT

Sensor/actuator cable SAC-3P-M8FY/2X0,3-PUR/M 8MS 1057311

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M8FY/2X0,3-PUR/M 8MS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M8FY/2X0,3-PUR/M 8MS
Catalog number	1057311
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-FD9424667E
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-3P-M8FY/2X0,3-PUR/M 8MS - 1057311

Sensor/Actuator Cable, 3-Pole Halogen-Free, Straight Female M8, Coding: A, A Straight Connector M8, Coding: A and Straight Connector M8, Coding: A, Cable Length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Socket straight M8, on Plug straight M8 and Plug straight M8, cable length: 0.3 m

Key Commercial Data

Orderkey 1057311

Packing unit 1

GTIN 4055626700021

Custom tariff number 85444290

Dimensions

Length of cable 0.3 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 3

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M8 connector IEC 61076-2-104

Status display No

Overvoltage category II

Degree of pollution 3

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M8 connector

Standards/regulations IEC 61076-2-104

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF

UL AWM style 20549

Conductor cross section $3 \times 0.25 \text{ mm}^2$

AWG signal line 24

Conductor structure signal line $32 \times 0.10 \text{ mm}$ Core diameter including insulation $1.17 \text{ mm} \pm 0.02 \text{ mm}$ Thickness, insulation $\geq 0.21 \text{ mm}$ (Core insulation)

Wire colors brown, blue, black

Overall twist 3 wires, twisted

Length of twist, overall twist 40 mm

External sheath, color black-gray RAL 7021

Ou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M8FY/2X0,3-PUR/M 8MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.