

INDUSTRIAL COMPONENT DATA

SAC-3P-M8MS/3,0-PUR/4PM12FS 42 1422319 PHOENIX CONTACT Sensor/actuator cable

SAC-3P-M8MS/3,0-PUR/4PM12FS 42 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M8MS/3,0-PUR/4PM12FS 42



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M8MS/3,0-PUR/4PM12FS 42
Catalog number	1422319
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-DF2E732AC5
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-3P-M8MS/3,0-PUR/4PM12FS 42 - 1422319

Sensor/actuator cable, 3-pole, halogen-free PUR, grayish black RAL 7021, Straight male connector M8, to Straight connection female M12, coding: A, cable length: 3 m

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M8, coding: A, on Socket straight M12, coding: A, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 3

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Outer sheath, material PUR
Conductor material Bare Cu litz wires
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Max. conductor resistance $77.6 \text{ m}\Omega/\text{m}$
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
Max. bending cycles 4000000
SignalingStatus display no
Status display present No
ConnectorConnection 1
Type Plug straight M8
Number of positions 3
Coding type A
Connection 2
Type Socket straight M12
Number of positions 3
Coding type A
Cable/lineCable length 3 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 18 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 3
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 32x 0.10 mm
AWG signal line 24
Conductor cross section 3x 0.25 mm² (Signal line)
Wire diameter incl. insulation 1.17 mm $\pm 0.02 \text{ mm}$
External cable diameter 3.60 mm $\pm 0.15 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M8MS/3,0-PUR/4PM12FS 42 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.