

INDUSTRIAL COMPONENT DATA

FTPC 12+1 3069268 PHOENIX CONTACT Test plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTPC 12+1



Manufacturer	PHOENIX CONTACT
MPN / Reference	FTPC 12+1
Catalog number	3069268
Category	Test plug for terminal blocks
Minimum order	1 Pcs
Document ID	EO-F89A98EF1C
Generated	2026-08-06

Product Overview

Test plug

Test connector, rated voltage: 400 V, rated current: 24 A, number of poles: 13, connection type: Screw connection, Sizing cross-section: 2.5 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 3069268

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 593 (C-1-2017)

GTIN 4055626380032

Weight per Piece (excluding packing) 491.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 13

Potentials 13

Nominal cross section 6 mm²

Color gray

Insulating material PA
Flammability rating according to UL 94 V0
Maximum load current 24 A
Maximum power dissipation for nominal condition 1.31 W
Maximum load current 24 A
Nominal current IN 24 A
Nominal voltage UN 400 V
Insertion/withdrawal cycles mechanical 500
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Note regarding shock protection When plugged in
Result of surge voltage test Test passed
Surge voltage test setpoint 4.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.2 mm² / 0.2 kg
6 mm² / 1.4 kg
10 mm² / 2 kg
Tensile test result Test passed
Conductor cross section tensile test 0.2 mm²
Tractive force setpoint 10 N
Conductor cross section tensile test 6 mm²
Tractive force setpoint 80 N
Conductor cross section tensile test 10 mm²
Tractive force setp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTPC 12+1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.