

INDUSTRIAL COMPONENT DATA

SAC-3P-MR/BI-1L-Z SCO 180 1409724 PHOENIX CONTACT

Valve connector, 3-pin, male Connector right angle M12, a-..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-MR/BI-1L-Z SCO 180



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-MR/BI-1L-Z SCO 180
Catalog number	1409724
Category	Valve connector (field assembly)
Minimum order	25 Pcs
Document ID	EO-BE825293E1
Generated	2026-08-06

Product Overview

Valve connector, 3-pin, male Connector right angle M12, a-coded, On valve Connector BI (11 mm), with 1 LED, connected with Diode Z, Face of connector plug valve rotated 180°

Valve connector, 3-pole, M12 angled connector, coding: A, with 1 LED, connected with Z Diode, to BI valve connectors (11mm), with 1 LED, connected with Z Diode, Valve connector plug face rotated 180°

Valve connector, 3-pole, M12 angled connector, coding: A, with 1 LED, Circuit: Z diode, a BI valve connectors (11 mm), with 1 LED, Circuit: Z diode, Valve connector plug face rotated 180°

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataItem PropertiesProduct Type Valve Connector Adapter

Number of poles 3

Number of Cable Outlets 1

Codification to

Data Maintenance Status

Article Review 02

Insulation Properties

Surge Category II

Degree of pollution 3

Connection dataConnection type M12 connector

Tightening torque 0.6 Nm (Valve Connector)
Electrical PropertiesInsulation resistance $\geq 100\text{ M}\Omega$
Nominal voltage UN 24 V AC
24 V DC
Nominal Current IN 4 A
Mechanical PropertiesMechanical data
Plug Cycles ≥ 100
Material DataFlammability class according to UL 94 HB
Gasket material TPU
Valve connector housing material TPU
Contact material CuSn
Material: Contact Surface Ni/AU
Contact Support Material PA 66
Contact material CuSn
Material: Insert Contacts Valve Connector AP 6.6
Material: Contact Surface Sn
Screw connection material Zinc die-cast iron, nickel-plated
SignageStatus Indication LED (yellow)
Available Status Indication Yes
ConnectorsConnection 1
Construction M12 Angled Connector
Number of poles 3
Encoding Type to
Connection 2
Construction BI Valve Connectors (11 mm)
Number of poles 3
Material CuSn (Contact)
Sn (Surface Contacts)
PA 6.6 (Contact Support)
TPU (Shell)
Environmental and life-life conditionsEnvironmental conditions
Protection Index IP65
IP67
Ambient Temperature (Service) $-25^{\circ}\text{C} \dots 85^{\circ}\text{C}$ (valve connector)
Standards & SpecificationsM12
Denomination of standard M12 connector
Rules/Provisions IEC 61076-2-101
ETIM for 1409724 Sensors (EC003623)
Feature Name
Feature Value
Number of poles (EF001391...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-MR/BI-1L-Z SCO 180 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.