

INDUSTRIAL COMPONENT DATA

SAC-3P-MS/0,4-28R SCO RAIL 1441171 PHOENIX CONTACT

Sensor/actuator cable, 3-pole, halogen-free PE-X, black, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-MS/0,4-28R SCO RAIL



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-MS/0,4-28R SCO RAIL
Catalog number	1441171
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-9D555F6B6B
Generated	2026-08-02

Product Overview

Sensor/actuator cable, 3-pole, halogen-free PE-X, black, shielded, M12 SPEEDCON straight connector, coding: A, to free cable end, cable length: 0.4 m, For railway applications
Cable for sensors/actuators

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1441171 Sensors (EC001855)
Feature Name
Feature Value
Number of poles (EF001391)
3
Type of electrical connection, field-sided (EF005525)
M12
Type of plug-in contact, field sided (EF006269)
Male (plug)
Positioning cable feed, field-sided (EF005928)
Straight
Type of electrical connection, box-sided (EF005524)
Other

Positioning cable feed, box-sided (EF005927)

Other

Cable length (EF000536)

0.4 m

Material of cable sheath (EF004136)

Other

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Black

With LED indication (EF005950)

No

Screened (EF000881)

Yes

Cable type (EF000081)

Multi-core

Vulcanize (EF004115)

No

Material contact body (EF008248)

CuSn

Material of contact surface (EF004020)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-50 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-25 °C

Rated current In (EF008250)

4 A

Rated voltage (EF000228)

48 V

Degree of protection (IP) (EF005474)

IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-MS/0,4-28R SCO RAIL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.