

INDUSTRIAL COMPONENT DATA

SAC-3P-MS/0,8-240/A SCO J-YM 1410060 PHOENIX CONTACT

Sensor/actuator cable SAC-3P-MS/0,8-240/A SCO J-YM 1410..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-MS/0,8-240/A SCO J-YM



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-MS/0,8-240/A SCO J-YM
Catalog number	1410060
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-2A24D4D302
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-3P-MS/0,8-240/A SCO J-YM - 1410060

Sensor/actuator cable, 3-pole halogen-free, M12 straight connector, coding: A SPEEDCON, a Valve connectors A, cable length: 0.8 m, Customer variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, yellow, Plug straight M12 SPEEDCON, A-coded, on Valve connector A, cable length: 0.8 m, Customer version

Key Commercial Data

Orderkey 1410060

Packing unit 1

GTIN 4046356888684

Custom tariff number 85444290

Dimensions

Length of cable 0.8 m

Ambient conditions

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Overvoltage category III
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU
Valve plug contact material CuSn
Valve plug contact surface material Sn
Valve plug contact insert material PA 6.6
Material housing valve plug TPU
Material, knurls Zinc die-cast, nickel-plated
Sealing material TPU (Seal molded)
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free yellow
Cable type (abbreviation) 240
Cable abbreviation Li9Y11Y
UL AWM style 20549 (80°C/300 V)
Conductor cross section $3 \times 0.5 \text{ mm}^2$
AWG signal line 20
Conductor structure signal line $28 \times 0.15 \text{ mm}$
Core diameter including insulation $1.46 \text{ mm} \pm 0.02 \text{ mm}$
Thickness, insulation $\geq 0.21 \text{ mm}$
Wire colors black 1, black 2, green/yellow
Overall twist 3 wires, twisted
External sheath, color yellow
Outer sheath thickness approx. 0.6 mm
External cable diameter $D 4.5 \text{ mm} \pm 0.15 \text{ mm}$
Cable weight 30 kg/k...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-MS/0,8-240/A SCO J-YM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.