

INDUSTRIAL COMPONENT DATA

SAC-3P-MS/1,3-PUR/A-1L-Z SCO 1401438 PHOENIX CONTACT Cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-MS/1,3-PUR/A-1L-Z SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-MS/1,3-PUR/A-1L-Z SCO
Catalog number	1401438
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-35C98E6661
Generated	2026-08-05

Product Overview

Cable

Sensor/actuator cable, 3 poles, halogen-free PUR black, straight male connector SPEEDCON M12 to A-construction valve connector, with 1 LED and Z-diode, cable length: 1.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1401438

Packing unit 1

GTIN 4046356555456

Custom tariff number 85444290

Dimensions

Length of cable 1.3 m

Ambient conditions

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 24 V AC

24 V DC
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display 1 LED
Protective circuit/component Z diode
Overvoltage category III
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU
Valve plug contact material CuSn
Valve plug contact surface material Sn
Valve plug contact insert material PA 6.6
Material housing valve plug TPU
Material, knurls Zinc die-cast, nickel-plated
Sealing material TPU (Seal molded)
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section $3 \times 0.5 \text{ mm}^2$
AWG signal line 20
Conductor structure signal line $28 \times 0.15 \text{ mm}$
Core diameter including insulation $1.5 \text{ mm} \pm 0.05 \text{ mm}$ (Signal line)
Wire colors black 1, black 2, green/yellow
Overall twist 3 wires, twisted
External sheath, color black-gray RAL 7021
External cable diameter $D 4.5 \text{ mm} \pm 0.2 \text{ mm}$
Smallest bending radius, fixed installation 22.5 mm
Number of bending cycles 15000000
Bending radius 50 mm
Traversing path 0.9 m
Traversing rate 5 m/s
Acceleration 30 m/s^2
Oute...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-MS/1,3-PUR/A-1L-Z SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.