

INDUSTRIAL COMPONENT DATA

SAC-3P-MSS/ 3,0-PVC PE SCO 1423702 PHOENIX CONTACT

Power cable SAC-3P-M12MSS/ 3,0-PVC PE 1423702

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-MSS/ 3,0-PVC PE SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-MSS/ 3,0-PVC PE SCO
Catalog number	1423702
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-BF58C44896
Generated	2026-08-06

Product Overview

Power cable - SAC-3P-M12MSS/ 3,0-PVC PE - 1423702

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Power cable, 3-position, PVC, black, Plug straight M12, S-coded, on free cable end, cable length: 3 m, for AC current up to 16 A/230 V

Key Commercial Data

Orderkey 1423702

Packing unit 1

GTIN 4055626352329

Custom tariff number 85444290

Dimensions

Length of cable 3 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP65

IP67

General

Rated current at 40°C 16 A

Rated voltage 230 V AC
230 V DC
Number of positions 3
Color handle area black
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding S power
Standards/regulations M12 connector IEC 61076-2-111
Status display No
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles > 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 V0
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA
Material of grip body PA
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-111
Flammability rating according to UL 94 V0
Cable
Cable type PVC black
Cable type (abbreviation) PVC
Cable abbreviation LSYwYw-JZ
UL AWM style 2517 (105 °C / 300 V)
Conductor cross section $3 \times 1.5 \text{ mm}^2$
AWG power supply 16
Conductor structure, voltage supply $30 \times 0.25 \text{ mm}$
Core diameter including insulation $2.4 \text{ mm} \pm 0.1 \text{ mm}$
Wire colors black 1, black 2, green/yellow
Overall twist 3 wires, twisted
External sheath, color black
External cable diam...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-MSS/ 3,0-PVC PE SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.