

INDUSTRIAL COMPONENT DATA

SAC-3P-Y/2X0,25-240/FS SCO 1426497 PHOENIX CONTACT

Cable for sensors/actuators, 3-pole, PUR halogen-free, ye..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-Y/2X0,25-240/FS SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-Y/2X0,25-240/FS SCO
Catalog number	1426497
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-3EF392EBCA
Generated	2026-08-05

Product Overview

Cable for sensors/actuators, 3-pole, PUR halogen-free, yellow, male Connector straight M12 SPEEDCON, coded, to the connection socket straight M12 SPEEDCON, encrypted and connection socket straight M12 SPEEDCON, coded, cable length: 0.25 m

Sensor/actuator cable, 3-pole halogen-free, M12 straight connector, coding: A SPEEDCON, a straight female M12, coding: A SPEEDCON and Straight female M12, coding: A SPEEDCON, cable length: 0.25 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cables, 3-pole, halogen-free PUR, yellow, M12 SPEEDCONNEC straight connector, keying A, on M12 SPEEDCONNEC straight female connector, keying A and M12 SPEEDCONNEC straight female connector, keying A, cable length: 0.25 m

Business Data

Order Code 1426497

Packaging unit 1

GTIN 4055626461298

Customs Tariff Number 85444290

Odds

Cable length 0.25 m

General

Reference voltage 48 V AC

60 V DC

Number of poles 3

Cable

Cable Type PUR halogen-free, yellow

Cable Type (Symbol) 240

Cable Symbol Li9Y11Y

Conductor Section 4x 0.34 mm²

AWG Signal Line 22

Conductor structure signal line 42x 0.10 mm

Wire diameter with insulation 1.27 mm ±0.02 mm

Insulation thickness ≥ 0.21 mm (Wire Insulation)
approx. 0.8 mm (outer sheath)

Yarn colours brown, white, blue, black

Total wiring 4 longitudinally twisted wires

No wiring, total wiring 49.5 mm

Outer sheath, colour yellow

Cable Outer Diameter D 4.7 mm ±0.15 mm

Minimum bending radius, fixed installation 23.5 mm

Minimal bending radius, flexible installation 47 mm

Number of bending cycles 4000000

Bend Radius 47 mm

Race 10 m

Movement speed 3 m/s

Acceleration 10 m/s²

Cable Weight 30 kg/km

Outer Sheath, Material PURE

Wire Insulating Material PP

Conductive material Bare Cu Cord

Insulation resistance ≥ 1 G?·km (at 20°C)

Conductor resistance max. 58 ?/km (at 20 °C)

Rated cable voltage ≤ 300 V

Test Voltage Cable ≥ 3000 V

Special properties Drag chain compatible
silicone-free

Free of substances harmful to the application of coatings

Resistance to fl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-Y/2X0,25-240/FS SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.