


INDUSTRIAL COMPONENT DATA

SAC-3PQ-1,5-PUR/M 8FR 1671771 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3PQ-1,5-PUR/M 8FR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3PQ-1,5-PUR/M 8FR
Catalog number	1671771
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-A573763566
Generated	2026-08-06

Product Overview

Sensor/actuator cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1671771

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 85 (PC-2002)

GTIN 4017918154981

Weight per Piece (excluding packing) 37.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 1.5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 3

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Status display No

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y

UL AWM style 20549

Conductor cross section $3 \times 0.34 \text{ mm}^2$ (Signal line)

AWG signal line 22

Conductor structure signal line $42 \times 0.10 \text{ mm}$

Core diameter including insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$ (Signal line)

Thickness, insulation $\geq 0.21 \text{ mm}$ (Core insulation)

approx. 0.5 mm (Outer cable sheath)

Wire colors brown, blue, black

Overall twist 3 wires, twist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3PQ-1,5-PUR/M 8FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.