

INDUSTRIAL COMPONENT DATA

SAC-4P-0,075-PUR/FS SCO 0,08 1425577 PHOENIX CONTACT

Sensor/actuator cable SAC-4P-0,075-PUR/FS SCO 0,08 1425..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-0,075-PUR/FS SCO 0,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-0,075-PUR/FS SCO 0,08
Catalog number	1425577
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-2EAA3F92D6
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-4P-0,075-PUR/FS SCO 0,08 - 1425577

Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12 SPEEDCON, coding: A, cable length: 0.075 m, Customer version

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 4

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Electrical propertiesNominal voltage UN 250 V AC

250 V DC

Nominal current IN 4 A

Connection dataConductor connection

Tightening torque 0.4 Nm

ConnectorConnection 1

Type free cable end

Connection 2

Type Socket straight M12 SPEEDCON
Number of positions 4
Locking type SPEEDCON
Coding type A
Cable/lineCable length 0.075 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 30 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 4
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm ±0.02 mm
External cable diameter 4.20 mm ±0.15 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, white, blue, black
Thickness, insulation ≥ 0.21 mm
Thickness, outer sheath approx. 0.50 mm
Overall twist 4 wires, twisted
Max. conductor resistance ≤ 58 Ω/km
Insulation resistance ≥ 1 GΩ*km
Nominal voltage, cable ≤ 300 V
Test voltage ≥ 3000 V
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 10 x D
Smallest bending radius, fixed installation 21 mm
Smallest bending radius, movable installation 42 mm
Dynamic load capacity...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-0,075-PUR/FS SCO 0,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.