

INDUSTRIAL COMPONENT DATA

SAC-4P-0,6-920/M12FSB X2X 1426309 PHOENIX CONTACT

Cable bus system

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-0,6-920/M12FSB X2X



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-0,6-920/M12FSB X2X
Catalog number	1426309
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-7971566938
Generated	2026-08-01

Product Overview

Cable bus system

Bus system cable, 4-pole, halogen-free PUR, lilac red RAL 4001, shielded, free cable end, a Straight female M12, coding: B, cable length: 0.6 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable bus system, 4-poles, without halogen free, violet, RAL 4001, shielded, cable length: 0.6 m

Commercial data

The code for the order One million four hundred twenty six thousand three hundred nine

Pieces/pack. 1 PCS

Sales key BF1CDD -

The amount of minimum order 50 PCS

GTIN Four trillion fifty five billion six hundred twenty six million four hundred fifty eight thousand seventy six

Weight per piece (package included) 58,000 g

Number customs tariff Eighty five million four hundred forty four thousand two hundred ninety

Size

Length. cable 0.6 m

General

Rated current at 40 °C 4 To

Rating voltage 48 V AC
60 V DC
N. of poles Four
Insulation resistance $\geq 100 \text{ M}\Omega$
Encoding B-coded
Signalling status of No
Overvoltage category II
Pollution degree Three
Material
Class behaviour according to UL 94 HB
Contact material CuSn
Material surface contacts Ni/Au
Insert material latch TPU GF
Material handles TPU, hardly inflammable, self-extinguishing
Nut material Zinc die-cast, nickel-plated
Material gasket NBR
Regulations and requirements
Class behaviour according to UL 94 HB
Cable
Cable type CAN BUS/DeviceNet
Cable type (abbreviation) Nine hundred twenty
UL AWM Style 21198 (80 °C / 300 V)
Structure cable 2xAWG24/19+2xAWG22/19
Conductor cross section 2x 0.25 mm² (data Line)
2x 0.34 mm² (power supply Voltage)
1x 0.34 mm² (flexible Conductors applied)
Signal line AWG Twenty four
Supply voltage AWG Twenty two
Tree conductor signal line 19x 0.13 mm
Structure conductor supply voltage 19x 0.15 mm
Wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-0,6-920/M12FSB X2X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.